

| Type | Capacity per hour | | Voltage (V) | Power compressor (kW) | Power PLC (V) | Fuse (A) | Plug (poles) | Phase | Noise (dB) | N ₂ receiver (Ltr) | N ₂ tube (mm) | No. of skids | Dimensions | | | Weight (kg) |
|---------|---------------------------------------|---|-------------|-----------------------|---------------|----------|--------------|-------|------------|-------------------------------|--------------------------|--------------|--------------|--------------|---------------|-------------|
| | 99% N ₂ (Nm ³) | 99,5% N ₂ (Nm ³) | | | | | | | | | | | A Width (mm) | B Depth (mm) | C Height (mm) | |
| UP1-4 | 4 | 3,2 | 400 | 1,5 | 230 | 16 | 5 | 3 | 64 | 200 | 12 | 1 | 1150 | 1150 | 1800 | 250 |
| UP1-6 | 6 | 4,8 | 400 | 2,2 | 230 | 16 | 5 | 3 | 70 | 200 | 12 | 1 | 1150 | 1150 | 1800 | 375 |
| UP1-8 | 8 | 6,4 | 400 | 3,0 | 230 | 16 | 5 | 3 | 70 | 200 | 12 | 1 | 1150 | 1150 | 1800 | 450 |
| UP1-12 | 12 | 9,6 | 400 | 4,0 | 230 | 16 | 5 | 3 | 71 | 200 | 12 | 1 | 1300 | 1350 | 1800 | 600 |
| UP1-17 | 17 | 13,6 | 400 | 4,0 | 230 | 16 | 5 | 3 | 71 | 270 | 12 | 1 | 1300 | 1350 | 1900 | 700 |
| UP1-22 | 22 | 17,6 | 400 | 5,5 | 230 | 16 | 5 | 3 | 71 | 270 | 32 | 1 | 1400 | 1400 | 1900 | 770 |
| UP1-33 | 33 | 26,4 | 400 | 7,5 | 230 | 25 | 5 | 3 | 75 | 500 | 32 | 1 | 1500 | 1600 | 2250 | 895 |
| UP1-48 | 48 | 38,4 | 400 | 11,0 | 230 | 32 | 5 | 3 | 75 | 500 | 32 | 1 | 1600 | 1600 | 2310 | 1066 |
| UP1-65 | 65 | 52,0 | 400 | 15,0 | 230 | 63 | Direct | 3 | 79 | 1000 | 32 | 1 | 1850 | 1900 | 2510 | 1700 |
| UP1-93 | 93 | 74,4 | 400 | 22,0 | 230 | 63 | Direct | 3 | 79 | 1000 | 32 | 1 | 2000 | 1925 | 2510 | 2400 |
| UP1-140 | 140 | 112,0 | 400 | 30,0 | 230 | 63 | Direct | 3 | 84 | 1000 | 50 | 3 | 1550 | 2150 | 2510 | 2095 |

Rev. 19-01 - Mentioned dimensions, weights and other specifications are approximate. No rights can be derived from this document.

